

OXXA[®]
PREMIUM



FIT




GRIP



DEXTERITY

X-PRO-FLEX

51-290



TOUCHSCREEN
CAPABILITY



CHARACTERISTICS

- NFT (Nitrile foam technology) coating on the palm and fingers
- Nylon/Lycra liner (15 gauge)
- Elastic knitted wrist cuff
- Seamless glove
- Good ventilation on the back of the hand
- Super light coating offers a high degree of fingertip sensitivity and flexibility
- Anti-slip by means of the Nitrile foam technology, the coating provides a good grip on dry, greasy and oily objects
- Their dark colour makes these gloves excellently suitable for use in environments with a certain level of contamination
- The conductive NFT coating on the palm and fingers allows the user to effortlessly operate touchscreen devices
- Sanitized[®] to inhibit bacterial growth, minimize odours and encourage freshness
- Free from harmful substances in accordance with OEKO-TEX[®] Standard 100

Article number: 1.51.290.00

SUITABLE FOR ACTIVITIES IN E.G.

- Construction
- Industry
- Installation technology
- Engineering
- Assembly
- Transport & logistics
- Automotive
- Maintenance

COLOUR

Black/grey

SIZES

7/S to 11/XXL incl.

PACKAGING

- 1 pair per headercard
- 12 pairs per bundle
- 144 pairs per outer box

EN388:2016

+A1:2018



4131X

EN407:2020



X1XXXX



EN ISO 21420:2020

PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (HEADERCARD)	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 144 PAIRS (OUTER BOX)
7/S	1.51.290.07	8718249011696	8718249011702	8718249011719
8/M	1.51.290.08	8718249011726	8718249011733	8718249011740
9/L	1.51.290.09	8718249011757	8718249011764	8718249011771
10/XL	1.51.290.10	8718249011788	8718249011795	8718249011801
11/XXL	1.51.290.11	8718249011818	8718249011825	8718249011832

COLOUR BINDING/OVERLOCKING

Sizes	7/S	8/M	9/L	10/XL	11/XXL
Colour binding/overlocking	yellow	green	blue	grey	black

CLARIFICATION OF PICTOGRAMS

EN388:2016
+A1:2018



4131X

EN388:2016
+A1:2018



abcdef

Protection against mechanical hazards

- A = Scuff resistance (0-4)
- B = Cut resistance (0-5)
- C = Tear resistance (0-4)
- D = Puncture resistance (0-4)
- E = Cut resistance (in accordance with EN ISO 13997 (A to F))
- F = Impact resistance (optional) (P = Passed)

EN 407:2020



X1XXXX

EN 407:2020



abcdef

Heat resistance

- A = Flammability (0-4)
- B = Contact heat (0-4)
- C = Convection heat (0-4)
- D = Radiation heat (0-4)
- E = Small droplets of molten metal (0-4)
- F = Large quantities of molten metal (0-4)

Note: X = untested or not applicable

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

These gloves are certified by: SATRA Technology Europe Ltd (Notified Body no. 2777), Bracetown Business Park, Clonee, Dublin D15 YN2P, Ireland.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa.work/doc

YOUR SUPPLIER:

RELATED PRODUCTS



X-PRO-FLEX 51-292
Art. no. 1.51.292.00



X-PRO-FLEX PLUS 51-295
Art. no. 1.51.295.00

