

**OXXA**<sup>®</sup>  
PREMIUM



FIT




GRIP



DEXTERITY

# X-PRO-FLEX PLUS

51-295



TOUCHSCREEN  
CAPABILITY



## CHARACTERISTICS

- NFT (Nitrile foam technology) coating on the palm and fingers
- Nylon/Lycra liner (15 gauge)
- Elastic knitted wrist cuff
- Seamless glove
- Features nitrile dots for an even better grip
- Super light coating offers a high degree of fingertip sensitivity and flexibility
- Anti-slip by means of the Nitrile foam technology, the coating provides a good grip on dry, greasy and oily objects
- Their dark colour makes these gloves excellently suitable for use in environments with a certain level of contamination
- The conductive NFT coating on the palm and fingers allows the user to effortlessly operate touchscreen devices
- Sanitised to inhibit bacterial growth, minimize odours and encourage freshness
- Free from harmful substances in accordance with OEKO-TEX<sup>®</sup> Standard 100

Article number: 1.51.295.00

## SUITABLE FOR ACTIVITIES IN E.G.

- Construction
- Industry
- Installation technology
- Engineering
- Assembly
- Transport & logistics
- Automotive
- Maintenance

## COLOUR

Black/grey

## SIZES

7/S to 11/XXL incl.

## PACKAGING

- 1 pair per polybag
- 12 pairs per bundle
- 144 pairs per outer box

EN388:2016  
+A1:2018



4131X

EN407:2004



X1XXX



EN ISO 21420:2020

## PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (POLYBAG)	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 144 PAIRS (OUTER BOX)
7/S	1.51.295.07	8718249011849	8718249011856	8718249011863
8/M	1.51.295.08	8718249011870	8718249011887	8718249011894
9/L	1.51.295.09	8718249011900	8718249011917	8718249011924
10/XL	1.51.295.10	8718249011931	8718249011948	8718249011955
11/XXL	1.51.295.11	8718249011962	8718249011979	8718249011986

## COLOUR BINDING/OVERLOCKING

Sizes	7/S	8/M	9/L	10/XL	11/XXL
Colour binding/overlocking	yellow	green	blue	grey	black

## CLARIFICATION OF PICTOGRAMS

EN388:2016  
+A1:2018



4131X

EN388:2016  
+A1:2018



abcdef

### Protection against mechanical hazards

- A = Scuff resistance (0-4)
- B = Cut resistance (0-5)
- C = Tear resistance (0-4)
- D = Puncture resistance (0-4)
- E = Cut resistance (in accordance with EN ISO 13997 (A to F))
- F = Impact resistance (optional) (P = Passed)

EN 407:2004



X1XXXX

EN 407:2004



abcdef

### Heat resistance

- A = Flammability (0-4)
- B = Contact heat (0-4)
- C = Convection heat (0-4)
- D = Radiation heat (0-4)
- E = Small droplets of molten metal (0-4)
- F = Large quantities of molten metal (0-4)

Note: X = untested or not applicable

## STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

## TESTING INSTITUTE

These gloves are certified by: SATRA Technology Europe Ltd (Notified Body no. 2777), Bracetown Business Park, Clonee, Dublin D15 YN2P, Ireland.

## DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: [www.oxxa.work/doc](http://www.oxxa.work/doc)

## YOUR SUPPLIER:

## RELATED PRODUCTS



**X-PRO-FLEX 51-290**  
Art. no. 1.51.290.00



**X-PRO-FLEX AIR 51-292**  
Art. no. 1.51.292.00