

**OXXA**<sup>®</sup>  
PREMIUM



FIT



GRIP



CUT  
RESISTANCE

# X-DIAMOND- PRO

51-770 **CUT B**



TOUCHSCREEN  
CAPABILITY



## CHARACTERISTICS

- Polyurethane coating on the palm and fingers
- Polyester/spandex/Dyneema<sup>®</sup> Diamond liner (18 gauge)
- Seamless glove
- Elastic knitted wrist cuff
- The ultra thin and light PU coating offers a high level of comfort, fingertip sensitivity and flexibility
- The 18-gauge knitted liner features Dyneema<sup>®</sup> Diamond Technology fibres, which offer very high cut resistance and excellent comfort
- Dyneema<sup>®</sup> Diamond is the strongest fibre in the world, allowing us to make very strong and cut-resistant safety gloves that are also very comfortable to wear
- Sanitised<sup>®</sup> treatment to inhibit bacterial growth, minimise odours and encourage freshness
- The conductive coating on the palm and fingers allows the user to effortlessly operate touchscreen devices

Article number: 1.51.770.00

## SUITABLE FOR ACTIVITIES IN E.G.

- Precision industry
- Glass industry
- Metal industry
- Paper industry
- Automotive
- Government services
- Assembly
- Machine maintenance

## COLOUR

Black/grey

## SIZES

7/S to 11/XXL incl.

## PACKAGING

- 1 pair per polybag
- 12 pairs per bundle
- 144 pairs per outer box

EN388:2016



3X42B



EN 420:2003+A1:2009

## PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (POLYBAG)	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 144 PAIRS (OUTER BOX)
7/S	1.51.770.07	8718249062131	8718249062148	8718249062155
8/M	1.51.770.08	8718249062162	8718249062179	8718249062186
9/L	1.51.770.09	8718249062193	8718249062209	8718249062216
10/XL	1.51.770.10	8718249062223	8718249062230	8718249062247
11/XXL	1.51.770.11	8718249062254	8718249062261	8718249062278

## COLOUR BINDING/OVERLOCKING

Sizes	7/S	8/M	9/L	10/XL	11/XXL
Colour binding/overlocking	yellow	green	blue	grey	black

## CLARIFICATION OF PICTOGRAMS

EN388:2016



3X42B

EN388:2016



abcdef

Protection against mechanical hazards

- A = Scuff resistance (0-4)
- B = Cut resistance (0-5)
- C = Tear resistance (0-4)
- D = Puncture resistance (0-4)
- E = Cut resistance (in accordance with EN ISO 13977 (A to F))
- F = Impact resistance (optional) (P = Passed)

Note: X = untested or not applicable

## STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

## TESTING INSTITUTE

These gloves are certified by: CTC (Notified Body no. 0075), 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France.

## DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: [www.oxxa-safety.com/doc](http://www.oxxa-safety.com/doc)

## YOUR SUPPLIER:

## RELATED PRODUCTS



**X-DIAMOND-PRO**  
**51-775 CUT C**

Art. no. 1.51.775.00



**X-DIAMOND-PRO**  
**51-785 CUT D**

Art. no. 1.51.785.00