



FIT




GRIP



COMFORT

E-MISSION-FLEX

52-200



24.HCN.11668
HOHENSTEIN HTTI



CHARACTERISTICS

- Nitrile micro foam coating on palm and fingers
- 58% Recycled polyester/polyester/Spandex backing (15 gauge)
- Seamless glove with an elastic knit wrist cuff
- Very good ventilation at the back of the hand keeping hands dry and cool
- Lightweight coating offers a high degree of dexterity and flexibility
- Nitrile micro foam coating provides very good grip on dry, greasy and oily objects
- Conductive coating on the fingers ensures perfect operation of all touchscreen devices
- Sanitized[®] treated to inhibit bacteria, minimize odors and promote freshness
- Free of harmful substances in accordance with OEKO-TEX[®] Standard 100

Article number: 1.52.200.00

SUITABLE FOR ACTIVITIES IN E.G.

- Automotive
- Construction
- Transport & logistics
- Installation technology
- Assembly

COLOR

Black/grey

MATEN

6/XS to 12/3XL

PACKAGING

- 1 pair per headercard
- 12 pairs per bundle
- 144 pairs per outer box

Sanitized[®]

EN388:2016
+A1:2018



4131X

EN407:2020



X1XXXX



TOUCHSCREEN
CAPABILITY



EN ISO 21420:2020

PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (HEADERCARD)	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 144 PAIRS (OUTER BOX)
6/XS	1.52.200.06	8718249079047	8718249079054	8718249079061
7/S	1.52.200.07	8718249070549	8718249070594	8718249070648
8/M	1.52.200.08	8718249070556	8718249070600	8718249070655
9/L	1.52.200.09	8718249070563	8718249070617	8718249070662
10/XL	1.52.200.10	8718249070570	8718249070624	8718249070679
11/XXL	1.52.200.11	8718249070587	8718249070631	8718249070686
12/3XL	1.52.200.12	8718249079078	8718249079085	8718249079092

PIPING COLOR

Sizes	6/XS	7/S	8/M	9/L	10/XL	11/XXL	12/3XL
Piping color	red	yellow	green	blue	gray	black	orange

CLARIFICATION OF PICTOGRAMS

EN388:2016
+A1:2018



4131X

EN388:2016
+A1:2018



ABCDEF

Protection against mechanical hazards

- A = Scuff resistance (0-4)
- B = Cut resistance (0-5)
- C = Tear resistance (0-4)
- D = Puncture resistance (0-4)
- E = Cut resistance (in accordance with EN ISO 13997 (A to F))
- F = Impact resistance (optional) (P = Passed)

EN407:2020



X1XXXX

EN407:2020



ABCDEF

Protection against heat and fire hazards

- A = Limited flame spread (0-4)
- B = Contact heat (0-4)
- C = Convection heat (0-4)
- D = Radiant heat (0-4)
- E = Small drops of molten metal (0-4)
- F = Large drops of molten metal (0-4)

Note: X = untested or not applicable

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

These gloves are certified by: CTC (Notified Body no: 0075), 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa.work/doc



YOUR SUPPLIER: