



LIQUID
PROOF




CUT
RESISTANCE



COLD
RESISTANCE

E-NATURE- WINTER-DRY

CUT D 52-855



OEKO
TEX[®]
STANDARD
100
15.HCN.75544
HOHENSTEIN HTTI

CHARACTERISTICS

- Glove with double latex coating
- RCS recycled nylon/HPPE/spandex backing (15 gauge) and a 'terry' acrylic liner (10 gauge)
- The combination of the fully smooth latex coating and latex 'Sandy Finish' on the palm and fingers provides superior grip in wet and dry conditions
- Dual latex coating makes this glove completely liquid-proof
- Highly flexible cut-resistant glove with good dexterity and seamless carrier for optimal comfort
- Warm acrylic liner makes the glove ideal for cold environments
- Extra long cuff ensures maximum protection of the wrist, the wrist
- Free of harmful substances according to OEKO-TEX[®] Standard 100

Article number: 1.52.855.00

SUITABLE FOR ACTIVITIES IN E.G.

- Construction
- Transport & logistics
- Industry
- Road construction
- Wet working conditions

COLOR

Black/dark green

SIZES

7/S to 12/3XL incl.

PACKAGING

- 1 pair per headercard
- 6 pairs per bundle
- 72 pairs per outer box

EN388:2016

+A1:2018

EN511:2006

EN407:2020



3X43D



X2X



X2XXXX



EN ISO 21420:2020

PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (HEADERCARD)	EAN CODE 6 PAIRS (BUNDLE)	EAN CODE 72 PAIRS (OUTER BOX)
7/S	1.52.855.07	8718249076855	8718249076909	8718249076954
8/M	1.52.855.08	8718249076862	8718249076916	8718249076961
9/L	1.52.855.09	8718249076879	8718249076923	8718249076978
10/XL	1.52.855.10	8718249076886	8718249076930	8718249076985
11/XXL	1.52.855.11	8718249076893	8718249076947	8718249076992
12/3XL	1.52.855.12	8718249079375	8718249079382	8718249079399

PIPING COLOR

Sizes	7/S	8/M	9/L	10/XL	11/XXL
Piping color	yellow	green	blue	gray	black

CLARIFICATION OF PICTOGRAMS

EN388:2016
+A1:2018



3X43D

EN388:2016
+A1:2018



ABCDEF

Protection against mechanical hazards

- A = Scuff resistance (0-4)
- B = Cut resistance (0-5)
- C = Tear resistance (0-4)
- D = Puncture resistance (0-4)
- E = Cut resistance (in accordance with EN ISO 13977 (A to F)
- F = Impact resistance (optional) (P = Passed)

EN407:2020



X2XXXX

EN407:2020



ABCDEF

Protection against heat and fire hazards

- A = Limited flame spread (0-4)
- B = Contact heat (0-4)
- C = Convection heat (0-4)
- D = Radiant heat (0-4)
- E = Small drops of molten metal (0-4)
- F = Large drops of molten metal (0-4)

EN511:2006



X2X

EN511:2006



ABC

Cold protection

- A = Radiant cold (0-4)
- B = Contact coldness (0-4)
- C = Waterproofness (0-1)

Note: X = Not tested or not applicable

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

These gloves are certified by: CTC (Notified Body no: 0075), 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa.work/doc

RELATED PRODUCTS



E-NATURE-DRY
CUT C 52-060

Art. no. 1.52.060.00

YOUR SUPPLIER: