OXXA®
PREMIUM

COMFORT
FLAME RETARDENT
SENSITIVITY

X-WELDER-PRO
53-800

CHARACTERISTICS
- Welding glove made from extremely supple bovine grain leather (0.9-1.0 mm) and cowhide split leather (1.1-1.2 mm)
- Five-fingered design
- Kevlar thread stitching
- Extended hood
- Bovine grain leather palm and cowhide split leather back
- Padded palm for increased comfort and protection and palm reinforcement
- Inserted ("Keystone") thumb for an optimally anatomic design
- Heavy fleece lining
- Suitable for general welding work
- Free of Chromium VI

Article number: 1.53.800.00

SUITABLE FOR ACTIVITIES IN E.G.
- Industry
- Offshore
- Metal industry
- Shipbuilding
- Construction
- Automotive

COLOUR
Natural/brown

SIZES
9/L to 11/XXL incl.

PACKAGING
- 6 pairs per bundle
- 60 pairs per outer box

EN 388:2016 +A1:2018
3243X

EN 407:2020
413244

EN 12477:2001 +A1:2005
Type A

CE 0075
EN ISO 21420:2020

Disclaimer: The user is responsible for the choices they make on the grounds of the information provided by OXXA® in this document. This information should therefore not be deemed conclusive when we refer to the suitability of the product for specific applications. OXXA® reserves the right to make chances to the products shown on this product sheet. The colours of the products shown on this product sheet may differ slightly in reality. Printing and typesetting errors reserved.

oxxa.work

Copyright © 2021 OXXA Safety Products, All rights reserved - **Version 2, 11-08-2025**

OXXA®

PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 6 PAIRS (BUNDLE)	EAN CODE 60 PAIRS (OUTER BOX)
9/L	1.53.800.09	8718249067266	8718249067273
10/XL	1.53.800.10	8718249041846	8718249041853
11/XXL	1.53.800.11	8718249041877	8718249041884

CLARIFICATION OF PICTOGRAMS

EN 388:2016 +A1:2018

3243X

EN 388:2016 +A1:2018

abcdef

Protection against mechanical hazards
A = Scuff resistance (0-4)
B = Cut resistance (0-5)
C = Tear resistance (0-4)
D = Puncture resistance (0-4)
E = Cut resistance (in accordance with EN ISO 13997 (A to F)
F = Impact resistance (optional) (P = Passed)

EN 407:2020

413244

EN 407:2020

abcdef

Heat resistance
A = Flammability (0-4)
B = Contact heat (0-4)
C = Convection heat (0-4)
D = Radiation heat (0-4)
E = Small droplets of molten metal (0-4)
F = Large quantities of molten metal (0-4)

Note: X = untested or not applicable

EN 12477:2001 +A1:2005

Type A

EN 12477:2001 +A1:2005

Type A/B

Protective glove for welders
Type A = for high-temperature welding activities (MIG/MAG)
Type B = for low-temperature welding activities (TIG)

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

These gloves are certified by: CTC (Notified Body no: 0075), 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: **www.oxxa.work/doc**

YOUR SUPPLIER:

Disclaimer: The user is responsible for the choices they make on the grounds of the information provided by OXXA® in this document. This information should therefore not be deemed conclusive when we refer to the suitability of the product for specific applications. OXXA® reserves the right to make chances to the products shown on this product sheet. The colours of the products shown on this product sheet may differ slightly in reality. Printing and typesetting errors reserved.

Copyright © 2021 OXXA Safety Products, All rights reserved - **Version 2, 11-08-2025**