

CHARACTERISTICS

- \cdot Safety glasses with smoke lens and black/lime frame
- $\cdot \ \mathsf{Polycarbonate} \ \mathsf{lenses}$
- \cdot 3 in 1 design, comes with foam edge and elastic band. Temples are easy to remove and replace with the elastic strap
- \cdot Completely metal-free safety glasses
- Extended temples to prevent the glasses from slipping and an even better fit
- $\boldsymbol{\cdot}$ Soft and flexible nose bridge for optimum comfort
- · 10 base lens curvature for optimal wrap-around
- Anti-fog coating and anti-scratch coating (according to marking KN certified)
- · UV400 protection
- \cdot Comes with an OXXA microfiber goggle pouch
- \cdot Packed individually in a beautiful unit box with hanging option
- · Weight: 31 grams
- · Lens Marking: 5-2.5 0 1 FT KN CE

Article number: 7.78.231.00

SUITABLE FOR ACTIVITIES IN E.G.

- $\cdot \ {\tt Construction}$
- Petrochemistry
- · Laboratories
- · Metal industry
- · Transport & logistics
- · Automotive
- · Maintenance
- · Construction

COLOUR

Smoke lens

OVERIGE BESCHIKBARE KLEUREN

X-Spec-Sporty 8230, clear lens (article number: 7.78.230.00)

SIZES

One size

PACKAGING

- · 1 piece per unit box
- · 12 piecesperinnerbox
- · 144 pieces per outer box

C E N 166:2001



PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN-CODE 1 PIECE (UNIT BOX)	EAN-CODE 12 PIECES (INNER BOX)	EAN-CODE 144 PIECES (OUTER CARTON)	
One size	7.78.231.00	8718249069314	8718249069352	8718249069390	



MARKINGS ON LENSES AND FRAMES

According to EN 166:2001, the safety glasses can have the following markings on the frame and lenses. They are explained below:

5-	1.7	1	F	EN 166:2001	3	9	к	N	CE
Α	В	D	E	F		(3		Н

A - Filter properties	D - Optical class	G - Application areas
2 - UV influence on color	1 (best) to 3	None - Basic (unspecified mechanical hazards and hazards
2C - UV protection with good color rendering 4 - IR 5 - Sun glare no IR 6 - Solar glare with IR B - Color number 1.2 (lightest) to 16 C - Manufacturer	E - Mechanical strength None - Minimal robustness S - Increased robustness F - Particle impact protection with low energy B - with medium energy A - with high impact energy T - at extreme temperatures (-5°C / 55°C) F - Default number	ue to ultraviolet, visible, infrared and solar radiation) 3 - Liquids (droplets and splashes) 4 - Large dust particles (dust with a particle size of >5 μm) 5 - Gas and fine dust (gases, vapours, sprays, smoke and dust with a particle size <5 μm) 8 - Short-circuit arc (arc due to short circuit in electrical devices) 9 - Molten metals and hot solids (molten metal splash and hot solids penetration) K - Resistance to damage by fine particles N - Resistance to fogging
identification		H - CE-marking
		According to European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE)

anti-fog glasses with a soft cloth only. Like all protective products, the life of safety glasses depends on use, care, maintenance and storage conditions. Replace scratched or damaged goggles. Replace the entire product if the frame is damaged. We recommend that unused spectacles and safety goggles be stored in a suitable case or in their original packaging. Like all other PPE, the life of this item depends on use, care and maintenance.

TESTING INSTITUTE

These safety glasses are certified by:SGS FIMKO OY (Notified Body nr. 0598), Takomotie 8, FI-00380, Helsinki, Finland.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa.work.com/doc

WARNING!

If protection against high velocity particles at extreme temperatures is required, the selected goggles should be marked with the letter T directly after the impact letter, i.e. FT, BT or AT. If there is no T after the impact letter, the goggles should only be used against high velocity particles at room temperature. Safety glasses that protect against high velocity particles worn over standard optical glasses can transmit impact energy, creating a hazard to the wearer.

STORAGE AND MAINTENANCE

Store eyewear in a dry place at room temperature and away from direct sunlight and abrasive chemicals. Transport and store eyewear in the original packaging, temperature range 5 °C - 40 °C, relative humidity <80%. Clean the glasses regularly. Do this with a mild detergent, at room temperature (20 \pm 5 °C). You can add a disinfectant to this cleaning solution according to the manufacturer's instructions. Clean

YOUR SUPLLIER:

