



Super abrasion resistance, great grip and additional durability. Touch screen function. 15 gauge, nitrile.

## KEY FEATURES

- High quality nitrile dots contribute to super abrasion resistance, great grip and additional durability
- 10-finger touch screen functionality enables you to use all touch screen devices on the jobs
- Super flexible, soft and comfortable
- Hi-vis orange colour
- 360° breathability
- Individual pack available for retail shops



## PRODUCT DETAILS

Liner	Polyester
Gauge	15
Coating	Nitrile
Finishing	Foam & Dotted
Colour	Orange / Black & Orange
Size	6,7,8,9,10,11,12
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020


## RECOMMENDED APPLICATIONS

General purpose work under dry, little wet/little oily working conditions.

Such as assembly and disassembly works, general handling, logistics, maintenance, inspection, sorting, machine operating, screwing, warehouse works...



## CERTIFICATION

 EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:  
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4): **4**  
Blade cut - coupe test (Index) (min.0 to max. 5): **1**  
Tear (min.0 to max. 4): **3**  
Puncture (min.0 to max. 4): **1**  
Cut resistance from sharp objects EN ISO  
13997:1999 (min. 0 to max. F, X - not tested): **A**  
Impact protection (P if pass, F if failed): **-**

EN388:2016



4131A

**EN407:2020 Heat protection:  
levels obtained in laboratory tests**

A - Limited flame spread: X of 4  
B - Contact heat: 1 of 4  
C - Convective heat: X of 4  
D - Radiant heat: X of 4  
E - Small splashes of molten metal: X of 4  
F - Large quantities of molten metal: X of 4

EN407:2020



X1XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

## STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 3006 can normally be 5 years.

## CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

## WARNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.

