




Oil & water repellent. Flexible, dexterity and comfortable. Double nitrile coated.

KEY FEATURES

- Oil & water repellent.
- Thanks to sandy finishing, it offers super grip in both oily and dry working condition.
- Flexible, dexterity and comfortable.
- Good fitting.
- Contact heat protection up to 100 degree C.
- Individual pack available for retail shops.



STANDARD 100
Hohenstein HTTI

15
Gauge



PRODUCT DETAILS

Liner	Polyester
Gauge	15
Coating	Nitrile
Finishing	Flat & Sandy
Colour	Blue / Blue & Black
Size	7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose works with/without contact heat hazard in wet or oily conditions.

Such as general works contact with water or oil, assembly and disassembly, equipment maintenance, inspection, sorting, general handling, adjusting systems...



CERTIFICATION

CE EN ISO 21420:2020

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	4
Blade cut - coupe test (Index) (min.0 to max. 5):	1
Tear (min.0 to max. 4):	3
Puncture (min.0 to max. 4):	1
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	X
Impact protection (P if pass, F if failed):	-

EN388:2016



4131X

**EN407:2020 Heat protection:
levels obtained in laboratory tests**

A - Limited flame spread	X of 4
B - Contact heat:	1 of 4
C - Convective heat:	X of 4
D - Radiant heat:	X of 4
E - Small splashes of molten metal:	X of 4
F - Large quantities of molten metal:	X of 4

EN407:2020



X1XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 3009 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk. Please ensure the products are strictly used within their protection levels.

